

GUARDIAN

FALL PROTECTION



Product Name: Bull Ring Anchor

Part #: 00484; 00484-SS

Instruction Manual

Do not throw away these instructions!

Read and understand these instructions before using equipment!

Introduction	1
Applicable Safety Standards	1
Worker Classifications	1
Product Specific Applications	2
Limitations	2 - 3
Components and Specifications	3
Installation and Use	4
Maintenance, Cleaning, and Storage	5
Inspection	5
Inspection Log	5
Safety Information	6
Labels	7

Introduction

Thank you for purchasing a Guardian Fall Protection Bull Ring Anchor. This manual must be read and understood in its entirety, and used as part of an employee training program as required by OSHA or any applicable state agency.

This and any other included instructions must be made available to the user of the equipment. The user must understand how to safely and effectively use the Bull Ring Anchor, and all fall safety equipment used in combination with the Bull Ring Anchor.

User Information	
Date of First Use:	_____
Serial #:	_____
Trainer:	_____
User:	_____

Applicable Safety Standards

When used according to instruction specifications, this product meets or exceeds all applicable OSHA 1926 Subpart M, OSHA 1910, ANSI Z359.18-2017, and ANSI A10.32-2012 standards for fall protection. This product has been tested in compliance with the requirements of ANSI/ASSE Z359.7. Note that if installing with nails this product is compliant with OSHA only. Testing only covers hardware and does not extend to the anchorage or substrate to which this product is attached. Applicable standards and regulations depend on the type of work being done, and also might include state-specific regulations. Consult regulatory agencies for more information on personal fall arrest systems and associated components.

PRODUCT COMPLIANCE	OSHA 1910 & OSHA 1926 Subpart M	ANSI Z359.18 & ANSI A10.32
Nail Installations	YES	NO
Screw Installations	YES	YES

Worker Classifications



Understand the following definitions of those who work near or who may be exposed to fall hazards.

Qualified Person: A person with an accredited degree or certification, and with extensive experience or sufficient professional standing, who is considered proficient in planning and reviewing the conformity of fall protection and rescue systems.

Competent Person: A highly trained and experienced person who is ASSIGNED BY THE EMPLOYER to be responsible for all elements of a fall safety program, including, but not limited to, its regulation, management, and application. A person who is proficient in identifying existing and predictable fall hazards, and who has the authority to stop work in order to eliminate hazards.

Authorized Person: A person who is assigned by their employer to work around or be subject to potential or existing fall hazards.

It is the responsibility of a Qualified or Competent person to supervise the job site and ensure all applicable safety regulations are complied with.

Product Specific Applications



WARNING Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.



Personal Fall Arrest: Bull Ring Anchor may be used to support a MAXIMUM 1 PFAS for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



Restraint: Bull Ring Anchor may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.

Limitations

Fall Clearance: There must be sufficient clearance below the anchorage connector to arrest a fall before the user strikes the ground or an obstruction. When calculating fall clearance, account for a MINIMUM 3' safety factor, deceleration distance, user height, length of lanyard/SRL, harness stretch, and all other applicable factors.

Diagram shown is an example fall clearance calculation ONLY.

Swing Falls: Prior to installation or use, make considerations for eliminating or minimizing all swing fall hazards. Swing falls occur when the anchor is not directly above the location where a fall occurs. Always work as close to in line with the anchor point as possible. Swing falls significantly increase the likelihood of serious injury or death in the event of a fall.


Compatibility: When making connections with Bull Ring Anchor, eliminate all possibility of roll-out. Roll-out occurs when interference between a hook and the attachment point causes the hook gate to unintentionally open and release. All connections must be selected and deemed compatible with Bull Ring Anchor by a Competent Person. All connector gates must be self-closing and self-locking, and withstand minimum loads of 3,600 lbs. See the following for examples of compatible/incompatible connections:

Connector closed and locked to D-ring. **OK.**



Connector to integral lanyard. **NO.**

Fall clearance calculation shown based on standing worker falling directly in-line with anchor point. Always consider potential swing fall and other hazards when calculating fall clearance.



Two connectors to same D-ring. **NO.**



Connector directly to webbing. **NO.**

Incompatible or irregular application, which may increase risk of roll-out. **NO.**



Connector directly to horizontal lifeline. **NO.**


Two or more snap hooks or carabiners connected to each other. **NO.**



Correct Anchorage Positioning:

This chart details allowable working zones required to reduce risk of swing falls and improper side loading. ALWAYS adhere to information specified by chart.

Anchor Distance From Leading Edge (Y)	Working Distance Along Roof Edge (Either Direction) (X)	Working Angle From Perpendicular (θ)
6'	8'	53°
10'	9' - 9"	45°
15'	11' - 7"	38°
20'	13' - 3"	33°
25'	14' - 6"	30°
30'	16'	28°
35'	17' - 2"	26°
40'	18' - 3"	24°
45'	19' - 4"	23°
50'	19' - 10"	21°
55'	21' - 4"	21°
60'	22' - 3"	21°



For example, if the anchorage connector is 6' from the leading edge (Y), the working distance (X) is 8' in each direction from the perpendicular, which translates to a 53° working angle.


Components and Specifications

Type A anchorage connector.

Minimum permitted service temperature: -30° F.

5,000 lb. MBS (minimum breaking strength).

Materials: zinc-plated steel (00484) or stainless steel (00484-SS).



(6) 16d nails



00484:
(5) 1/4" x 3" zinc-plated steel hex head lag screws



00484-SS:
(5) 1/4" x 3" stainless steel hex head lag screws

Installation and Use

MINIMUM substrate thickness requirements:

- Wood: 3½" (total combined). DO NOT install on substrates other than wood.

Fastener requirements:

- (5) 1/4" x 3" steel hex head lag screws. -OR-
- (6) 16d nails. Minimum required nail head diameter: 11/32". Note that installation with nails is compliant with OSHA regulations only.

Compatible roof pitch:

- 0/12 - vertical/sheer. Never install past sheer (such as on underside of beam).

Prior to installation, plan your system:


1. Determine installation location of Bull Ring Anchor; ensure location is free of debris, rot, decay, cracking, and hazardous materials. Ensure selected installation location is a MINIMUM 2' from all leading edges. Ensure Bull Ring Anchor will lie flush with substrate. If unable to determine suitable installation location, consult jobsite Qualified Person.
2. Make considerations for eliminating or minimizing all swing fall hazards.
3. Ensure all fasteners are those supplied by Guardian Fall Protection, or are deemed compatible with Bull Ring Anchor by a Competent Person.
4. The Bull Ring Anchor is rated for loading in any direction provided it is installed as prescribed. Suitable for use in HLL applications; HLL must be installed perpendicular to long side of Bull Ring Anchor.

Installation:

1. To install, use either nails OR screws specified above. Fasteners must be fully embedded in substrate. Use proper fastener holes, shown below.
2. DO NOT apply torque to fasteners.
3. Bull Ring Anchor is suitable for multiple installation applications. New fasteners MUST be used for each new installation application.
4. Prior to each new installation, ensure Bull Ring Anchor is not damaged or warped by previous use. If any damage or defects are found, IMMEDIATELY remove Bull Ring Anchor from service.
5. Attach complete and compatible PFAS to Bull Ring Anchor connection point.



All (6) fasteners fully embedded into substrate
Nail Installation:
(6) 16d nails



All (5) fasteners fully embedded into substrate
Screw Installation:
(5) 1/4" x 3" steel hex head lag screws

Maintenance, Cleaning, and Storage

If Bull Ring Anchor fails inspection in any way, immediately remove it from service, and contact Guardian to inquire about its return or repair. Field serviceability testing is not required, and should not be done by the end user.

Cleaning after use is important for maintaining the safety and longevity of Bull Ring Anchor. Remove all dirt, corrosives, and contaminants from Bull Ring Anchor before and after each use. If Bull Ring Anchor cannot be cleaned with plain water, use mild soap and water, then rinse and wipe dry. NEVER clean Bull Ring Anchor with corrosive substances.

When not in use, store equipment where it will not be affected by heat, light, excessive moisture, chemicals, or other degrading elements.

Inspection

Prior to EACH use, inspect Bull Ring Anchor for deficiencies, including, but not limited to, corrosion, deformation, pits, burrs, rough surfaces, sharp edges, cracking, rust, paint buildup, excessive heating, alteration, and missing or illegible labels. IMMEDIATELY remove Bull Ring Anchor from service if defects or damage are found, or if exposed to forces of Fall Arrest.

Ensure that applicable work area is free of all damage, including, but not limited to, debris, rot, rust, decay, cracking, and hazardous materials. Ensure that selected work area will support the application-specific minimum loads set forth in this instruction manual. Work area MUST be stable.

At least every 6 months, a Competent Person other than the user must inspect Bull Ring Anchor. **Competent Person inspections MUST be recorded in inspection log in instruction manual and on equipment inspection grid label. The Competent Person must sign their initials in the box corresponding to the month and year the inspection took place.**

During inspection, consider all applications and hazards Bull Ring Anchor have been subjected to.

Inspection Log

Date of First Use: _____.

Product lifetime is indefinite as long as it passes pre-use and Competent Person inspections. User must inspect prior to EACH use. Competent Person other than user must complete formal inspection at least every 6 months. Competent Person to inspect and initial.

This inspection log must be specific to one Bull Ring Anchor. Separate inspection logs must be used for each Bull Ring Anchor. All inspection records must be made visible and available to all users at all times.

	J	F	M	A	M	J	J	A	S	O	N	D
YR												
YR												
YR												
YR												
YR												

If equipment fails inspection IMMEDIATELY REMOVE FROM SERVICE.

Safety Information



Failure to understand and comply with safety regulations may result in serious injury or death. Regulations included herein are not all-inclusive, are for reference only, and are not intended to replace a Competent Person's judgment or knowledge of federal or state standards.

Do not alter equipment. Do not misuse equipment.

Workplace conditions, including, but not limited to, flame, corrosive chemicals, electrical shock, sharp objects, machinery, abrasive substances, weather conditions, and uneven surfaces, must be assessed by a Competent Person before fall protection equipment is selected.

The analysis of the workplace must anticipate where workers will be performing their duties, the routes they will take to reach their work, and the potential and existing fall hazards they may be exposed to. Fall protection equipment must be chosen by a Competent Person. Selections must account for all potential hazardous workplace conditions. All fall protection equipment should be purchased new and in an unused condition.

Fall protection systems must be selected and installed under the supervision of a Competent Person, and used in a compliant manner. Fall protection systems must be designed in a manner compliant with all federal, state, and safety regulations. Forces applied to anchors must be calculated by a Competent Person.

Unless explicitly stated otherwise, the maximum allowable free fall distance for lanyards must not exceed 6'. No free fall allowed for non-LE SRLs. Class A SRLs must arrest falls within 24"; Class B SRLs must arrest falls within 54".

Harnesses and connectors selected must be compliant with manufacturer's instructions, and must be of compatible size and configuration. Snap hooks, carabiners, and other connectors must be selected and applied in a compatible fashion. All risk of disengagement must be eliminated. All snap hooks and carabiners must be self-locking and self-closing, and must never be connected to each other.

A pre-planned rescue procedure in the case of a fall is required. The rescue plan must be project-specific. The rescue plan must allow for employees to rescue themselves, or provide an alternative means for their prompt rescue. Store rescue equipment in an easily accessible and clearly marked area.

Training of Authorized Persons to correctly erect, disassemble, inspect, maintain, store, and use equipment must be provided by a Competent Person. Training must include the ability to recognize fall hazards, minimize the likelihood of fall hazards, and the correct use of Personal Fall Arrest Systems.

NEVER use fall protection equipment of any kind to hang, lift, support, or hoist tools or equipment, unless explicitly certified for such use.

Equipment subjected to forces of Fall Arrest must immediately be removed from use.

Age, fitness, and health conditions can seriously affect the worker should a fall occur. Consult a doctor if there is any reason to doubt a user's ability to withstand and safely absorb Fall Arrest forces or perform set-up of equipment. Pregnant women and minors must not use this equipment.

Physical harm may still occur even if fall safety equipment functions correctly. Sustained post-fall suspension may result in serious injury or death. Use trauma relief straps to reduce the effects of suspension trauma.

Labels

BULL RING ANCHOR

Part #: 00484 Made in China

DOM: Serial #:

OSHA 1926 Sub M, OSHA 1910, ANSI Z359.18-2017, and ANSI A10.32-2012.

PRIOR to use, read and understand all manufacturer's instructions included with the equipment.

Inspect prior to EACH use. Competent Person must inspect every 6 months, and record inspection in instruction manual and on equipment.

Worker capacity: 130-420 lbs.
Material: Zinc-plated steel
Type A anchorage connector.
5,000 lb. MBS
(minimum breaking strength).
Minimum service temp.: -30° F.
MAXIMUM 1 connection.
All connections must be compatible with the Bull Ring Anchor, and selected by a Competent Person.

INSTALLATION:
Use (5) 1/4" x 3" screws OR (6) 16d nails. See instructions.
Nail installation compatible with OSHA standards only.
Fully embed all fasteners into substrate.

	J	F	M	A	M	J	J	A	S	O	N	D
YR												
YR												
YR												
YR												
YR												

WARNING

IMMEDIATELY remove from service if exposed to forces of fall arrest. Avoid all contact with sharp and abrasive edges and surfaces. Avoid all contact with hazardous conditions including, but not limited to, high temperatures, electrical shock, and corrosive chemicals.

GUARDIAN
FALL PROTECTION

www.guardianfall.com

1-800-466-6385
6305 S. 231st St.
Kent, WA 98032
90003 (Rev. F)